



# RV926 Receiver Specifications

**V3.0** 



#### **Revision History**

Document	Hardware	Revision	Note
Version	Version	Date	
V3.0	V8	2020/1	New edition

#### Overview

RV926 is a standardize product for LED screen manufacturer, which is integrated with 16 standard hub75-type connectors and does not require an extra hub card. One card supports up to 512\*512pixels and up to 32 sets of RCG data.

#### **Functions and features**

- 1. Single card can support 32 group of RGB data output mode
- 2. Maximum supports 512X512(Please note that there are

recommended values depending on the design of LED screen pixels)


3. Supports brightness calibration pixel by pixel and single-card color

space conversion


- 4. Supports network cable BER test
- 5. Supports configuration file read back
- 6. Supports 138 decode, 595 serial decode and so on
- 7. Realizes high refresh and high gray level effect

Official website: www.linsn.com Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd, Nanshan District, Shenzhen Tel: +86-0755-86183590/ 4008836968










Official website: www.linsn.com Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd, Nanshan District, Shenzhen Tel: +86-0755-86183590/ 4008836968

Lins	n Technology
------	--------------

No.	1	2	3	4/9
Description	Gigabit port Power		Power port	Hub75
		connector		Connector
No.	5	6	7	8
Description	Red power	Green indicator	Self-test	Self-test button
	indicator		extension port	

#### **Pinouts**




/	R1	1	2	G1	/
/	B1	3	4	GND	GND
/	R2	5	6	G2	/
/	B2	7	8	Е	Row selection
					signal
Row selection	А	9	10	В	Row selection
signal					signal
Row selection	С	11	12	D	Row selection
signal					signal
Scan clock	CLK	13	14	LAT	Latch
Display enable	OE	15	16	GND	GND

Official website: www.linsn.com Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd, Nanshan District, Shenzhen Tel: +86-0755-86183590/ 4008836968



## Dimension



### **Specifications**

Capacity	512X512 Pixels	
	Input Voltage	DC4.5V ~ 5.5V
Power	Rated power	3.5W
	consumption	
Working	Temperature	-20℃~ 70℃

Official website: www.linsn.com

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd, Nanshan District, Shenzhen Tel: +86-0755-86183590/ 4008836968



Environment	Humidity	0% ~ 95%
Physical	Dimensions	144.0 X 91.2mm
Dimensions	Weight	110g
	Packing	Each card packed with small red foam
Packing		bag, and 100pcs per carton
Info	Carton Dimension	622.0mm×465.0mm×176.0mm
	Carton Weight	13.8 kg

END